

VJET 1000

Post Print Enhancement

SPOT UV VARNISH & FOILING



For Spot Varnish Printing As Post Treatment To Enhance Effect;

Easy, Fast & Accurate



PARAMETERS

Printhead	Drop-on-demand piezo, 1024 nozzles
Print width	350mm
Print Speed	15–20m/min
Varnish thickness	3D: Max. thickness to reach 110µm Min thickness to 40µm
Type	Coated paper, White cardboard Matt lamination, Soft Touch Film
Material width	≥ 210x297mm ≤ 320x460mm
Paper weight	135g/m ³ – 400g/m ³
Stacking height	25cm (≤2000pcs 135g/m ³)
Registration	Registration by CCD with position difference less than 0.2MM
Operation Environment	Temp: 18–30° C, Humidity: 40–70%
Power Specification	AC220V, 5.5KW
Printer Dimensions	L3305 x W1220 x H1620mm



☎ +91 97697 48399 | +91 93212 65387

🌐 www.shreejicorporation.org

📍 Shreeji Corporation, C-203, 2nd Floor, Synthofine Estate, Goregaon East, Mumbai - 400 063.
307, Palladium Business Hub, Opp. 4D Square Mall, Motera-Visat Road, Chandkheda, Ahmedabad - 382424.